

Celadon Inc.

RCV-5000 IR to RS-232 Output Table

Device: Fujitsu P50XCA Plasma Models

Infrared Remote Control: Philips PRONTO, Niles Intellicontrol

Infrared Code Format: NEC - Device ID: 7B02

Infrared Pronto Data File(s): See "IR Code Read Me - RCV-5000.txt" for complete description

Infrared Receiver: Celadon RCV-5000 Infrared to RS-232 Receiver

RCV-5000 Data File: fujitsu5_r.hex

Data: 4800 Baud, 8, N, 1, ASCII Output

NOTE: All ASCII Strings have Carriage Return Proceeding

TD Pin 2, RD Pin 3 (switched)

Fujitsu Function	Pronto Button	RCV-5000 Output
Connection Command	0	@G
Termination of Communication	1	@Q
Power Supply OFF	2	%A0000
Power Supply ON	3	%A0001
RGB_D-SUB - RGB1	4	%A1000
RGB_BNC - RGB2	5	%A1001
Video RCA input Video 1	6	%A1012
S-video input Video 2	7	%A1014
Aspect: NORMAL	8	%A1100
Aspect: WIDE1	9	%A1101
Aspect: WIDE2	10	%A1102
Aspect: ZOOM1	11	%A1103
Aspect: ZOOM2	12	%A1104

Celadon, Inc.

50 Mitchell Blvd.

San Rafael, CA 94903

Tel: (415) 472-1177

Fax: (415) 472-1179

sales@celadon.com